



BOULDIN & LAWSON, LLC

P.O. Box 7177
McMinnville, TN 37111
Phone: 931-668-4090
Toll Free : 800-443-6398
Fax: 931-668-3209

E-mail:
sales@bouldinlawson.com

www.bouldinlawson.com



Expanded plug on dibble unit



Optional Heating



A proud member of the
BouldinCorp™ Family

Jiffy - Plug Expander and Dibble Unit



The Expander is designed to expand the jiffy plug from its dry compressed state. Trays are placed at entry point, then sub-irrigated and sprayed from above at progressive stages until expanded. Production rate is 12 trays per minute and water temperature is preferred to be 130 degrees. The plugs then pass through the optional Dibble unit where the indentations are reformed and centered prior to seeding. Dibble unit uses B&L's quick-attach system, so it can be quickly connected and always lines up correctly. It can be purchased with the Expander or at a later date if and as required.

Compressed air at 90 psi is required for the Dibble unit and a hot water supply is required for the Expander. A digital display is included to monitor the water temperature and depth adjustment for the sub-irrigation.

Options include: Filtered recirculation tank, heating elements in both recirc tank and expander body. This helps maintain ideal temperature and reduce water usage



Before and after expansion



Dibble Unit



Filtered Recirculation



Made in the USA